

# Product Offerings



PRODUCTS		THICKNESS OR GAUGE (IN)	WIDTH (IN)	WEIGHT CAPACITY	COATING WEIGHT	GRADE	TEMPER	FINISHES
COLD-ROLLED CARBON STEEL		0.010 - 0.125	1.00 - 72	60,000 lbs	N/A	CS, DS, DDS, EDDS, SS, HSLA 35-80, JIS, SAE, BH, A109, C1004-C1020, AHSS	N/A	N/A
HOT-ROLLED CARBON STEEL		0.055 - 0.45	1.00 - 72	60,000 lbs	N/A	CS, DS, SS, HSLA 43-100, JIS, SAE, C1004-C1020, C1050, AHSS	N/A	P&O, Black, Dry Lube, Tension Leveled
PAINTED STEEL		0.010 - 0.07	1.00 - 72	60,000 lbs	Various	All structural strength grade products available (inquire for specific grade)	N/A	PVDF, SMP, Polyester
COATED STEEL	GALVALUME	0.010 - 0.025	1.00 - 72	60,000 lbs	AZ35 - AZ60	All structural strength grade products available (inquire for specific grade)	N/A	Min Spangle, Extra Smooth, Acrylic
	GALVANIZED	0.010 - 0.25	1.00 - 72	60,000 lbs	G30 - G235	CS, FS, DDS, EDDS, SS, HSLA 35-80, SAE, DP, BH, C1001-C1020, AHSS	N/A	Min Spangle, Extra Smooth, ROHS Chemical Treatment, Prelube, Acrylic
	GALVANNEAL	0.010 - 0.25	1.00 - 72	60,000 lbs	A25 - A60			
	ELECTROGALVANIZED	0.010 - 0.080	1.00 - 72	60,000 lbs	10g/10g - 60g/60g			
STAINLESS		0.005 - 0.500	0.090 - 72.00	60,000 lbs	N/A	201, 301, 304, 304L, 316, 316L, 321, 18CrCb, 409, 410, 410S, 430, 434, 439	Annealed through full hard	HRAP, 2D, 2B, #3, #4, #8, Bright Annealed
ALUMINUM		0.016 - 0.500	0.090 - 72	60,000 lbs	N/A	1100, 3003, 3104, 3105, 5052, 5182, 5754, 6061	O-Temp, H14, H22, H24, H32, H34, H38, T4, T6	Mill Finish, Diamond Tread Plate and Polished
METAL FRAMING		Cold Rolled Channel, Drywall Furring, Flat Strapping, Framing Clips & Connectors, ProSTUD®, ProTRAK®, USG Shaftwall, Resilient Channel, Slotted Slip Track, Utility Angle, Z-Furring, Area Separation						

# Capabilities



## Steel Slitting

---

- Thickness or Gauge: 0.010" - 0.75"
- Width: 0.375" - 74"
- Coil Max Weight: 75,000 lbs.
- OD Max: 78"

## Coil Polishing

---

- 61.25" Max Width
- .015 - .105 gauge Wet/Dry Finish
- 50,000 lb. max incoming coil
- 40,000 lb. max outgoing coil
- Ra approx. 8-10

## Cut-to-Length

---

- Width Max: 74"
- Gauge: 0.10 - 0.75"

## Heavy Gauge CTL

---

- 72" Max Width
- 24" min width
- 480" or longer length on application
- Stainless .140 - .375 gauge
- Aluminum .250 - .500 gauge
- 40,000 lb max coil
- 16" - 32" ID 84" Max OD
- Length tolerance +1/4" /- 0 on standard sizes

## Sheet/Plate Polishing

---

- 60" Max Width
- 18 ga thru .250 max
- 72" Min / 144" Max Length
- Ra approx. 14

## Precision Blanking

---

- 72" Max Width 192"
- Stacker Length (longer on application)
- Stainless .015 - .135 gauge
- Aluminum .016 - .190 gauge
- 60,000 lb Max Coil
- 20" Min ID
- 80" Max OD
- Standard length tolerance +1/16"/- .005